

Release Note for AT-VST-VRT Vista Manager Virtual 3.8.x



» 3.8. I



Acknowledgments

©2023 Allied Telesis Inc. All rights reserved. No part of this publication may be reproduced without prior written permission from Allied Telesis, Inc.

Allied Telesis, Inc. reserves the right to make changes in specifications and other information contained in this document without prior written notice. The information provided herein is subject to change without notice. In no event shall Allied Telesis, Inc. be liable for any incidental, special, indirect, or consequential damages whatsoever, including but not limited to lost profits, arising out of or related to this manual or the information contained herein, even if Allied Telesis, Inc. has been advised of, known, or should have known, the possibility of such damages.

Allied Telesis, AlliedWare Plus, Allied Telesis Management Framework, EPSRing, SwitchBlade, VCStack and VCStack Plus are trademarks or registered trademarks in the United States and elsewhere of Allied Telesis, Inc. Adobe, Acrobat, and Reader are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Additional brands, names and products mentioned herein may be trademarks of their respective companies.

Getting the most from this Release Note

To get the best from this release note, we recommend using Adobe Acrobat Reader version 8 or later. You can download Acrobat free from www.adobe.com/



Contents

VST-VRT Software Version 3.8.1	4
Introduction	.4
Application support in VST-VRT 3.8.1	.4
What's New in VST-VRT 3.8.1	.5
Upgrading VST-VRT	6
Backup application data	.6
Upgrade the VST-VRT operating system and GUI	.6
Upgrade Vista Manager, AMF Cloud, Trap Receiver and AMF Security applications	12
Upgrade Wireless Controller (AWC) and SNMP (full) plug-in applications	15



VST-VRT Software Version 3.8.1

Product family supported by this version: AT-VST-VRT Vista Manager Virtual

Introduction

The virtual machine version of Vista Manager is called Vista Manager Virtual (VST-VRT). VST-VRT includes the tools to simplify and centralize management and security of your network. It provides an integrated graphical view for monitoring and management of wired, wireless and third-party devices. The VST-VRT Web GUI allows you to manage the virtual machine and to set up and access applications that run on it.

This release note describes Vista Manager Virtual running VST-VRT software version 3.8.1 and the new software features in this version.

You obtain the VST-VRT software from the Software Download area of the Allied Telesis website. Log in using your assigned email address and password.

The VST-VRT upgrade is packaged as a .iso file. On the Software Download site, the VST-VRT file is located in the Network Management Software product category, under the Vista Manager 3.11.0 section. The file is named **VST_VRT-3.8.1.iso**.

This version of VST-VRT supports the following virtualization environments:

- Oracle VM VirtualBox version 5.2
- Oracle VM VirtualBox version 6.1

For full system requirements for VST-VRT see the Vista Manager EX datasheet.

Application support in VST-VRT 3.8.1

VST-VRT version 3.8.1 includes the following:

Software	VERSION
VST-VRT Operating System	1.8.3
Vista Manager	3.11.0
Wireless Controller (AWC)	3.11.0
SNMP-Full	2.10.0
AMF Cloud	5.5.3-1.3
AMF Security	2.6.0



What's New in VST-VRT 3.8.1

VST-VRT 3.8.1 includes the following support for new application versions, new features and enhancements.

Vista Manager

The Vista Manager application was upgraded to version 3.11.0. For release notes and other technical documents for Vista Manager, see the Vista Manager Virtual Technical Document page on our website.

Wireless Controller (AWC)

The Wireless Controller (AWC) application was upgraded to version 3.11.0. For release notes and other technical documents for Wireless Controller (AWC), see the Vista Manager Virtual Technical Document page on our website.

SNMP

The SNMP (full SNMP) plug-in application was upgraded to 2.10.0. For release notes and other technical documents for SNMP, see the Vista Manager Virtual Technical Document page on our website.

AMF Cloud

The AMF Cloud application was upgraded to version 5.5.3-1.3. For release notes and other technical documents for AMF Cloud, see the Vista Manager Virtual Technical Document page on our website.

AMF Security (AMF-Sec)

The AMF Security application was upgraded to 2.6.0. For release notes and other technical documents for AMF-Sec, see the Vista Manager Virtual Technical Documents page on our website.



Upgrading VST-VRT

This section describes how to:

- "Backup application data" below
- "Upgrade the VST-VRT operating system and GUI" below
- "Upgrade Vista Manager, AMF Cloud, Trap Receiver and AMF Security applications" on page 12
- "Upgrade Wireless Controller (AWC) and SNMP (full) plug-in applications" on page 15

Backup application data

We recommend backing up application data for all applications regularly. You should also backup all the application data before following this upgrade procedure. See the relevant application's user manual for information on how to backup an application.

If you are using the **Wireless Controller (AWC)** or the **SNMP (full)** plug-in applications, you must back up these applications before proceeding. This is because the process destroys and recreates the application instance. See "Upgrade Wireless Controller (AWC) and SNMP (full) plug-in applications" on page 15 for information on backing up these applications before you continue with following section.

Upgrade the VST-VRT operating system and GUI

To upgrade the VST-VRT operating system, follow these steps.

- 1. Get the latest version of the VST-VRT software from the Software Download Centre. This will have a filename like VST_VRT-x.x.x.iso, where x.x.x is the version. Download it to a directory that is visible to your VST-VRT virtual machine.
- 2. If you want to retain the current unsaved configuration of VST-VRT, login to the VST-VRT GUI and click the **Save** button on the top right of the page. This stores the current state of the applications. The upgrade process will reboot the VST-VRT.



3. On the machine your virtual machine is running on, open Oracle VM VirtualBox Manager.



4. Shut down your VST-VRT VM. To do this, right click on the VM, then select **Close**, and **ACPI Shutdown**.

😚 Oracle VM VirtualBox M	anager				_	×
File Machine Help						
Tools	N N	ew Settings Disc	ard Show			
MT-VST-VRT-x.x.x	[General		Preview		
200 € Running 6 9 	Settings Clone Move Export to OCl Remove Group	Ctrl+S Ctrl+O	-VST-VRT-x.x.x ux 2.6 / 3.x / 4.x (64-bit) MB , Hard Disk MD-V, Nested Paging, PAE/ V Paravirtualization	0 1 Statistic Relymping 0 1 Statistic R	hrms. Life shops q stiles.	
	Show Pause Reset		16 MB VMSVGA Disabled Disabled	Liberta darka tanan Manana di Maya Anana Manana di Maya darka di Anana Manana di Manana di Anana		
	Close Discard Saved State Show Log Refresh	Ctrl+L	Save State ACPI Shutdown Power Off AT-VST-VRT-x.x.x-disk0	.x.x.iso (1.06 GB) 01.vdi (Normal, 630.00	GB)	
	Show in Explorer Create Shortcut on De	sktop				
80	Sort					
<i>Q</i>	Search De	Ctrl+F evice Filters: 0 (0 a	active)			
		Shared folders	-			



5. Wait until the VM has finished shutting down. Its status will change to **Powered Off**.



6. Right click on the VM and select **Settings**.



7. Select the **Storage** tab of the **Settings** dialog.





8. Select your VST-VRT VM's optical drive. Make sure the **Live CD/DVD** checkbox is checked.



9. Click on the **Choose a virtual drive** drop-down, and select **Choose/Create Virtual Optical Disk...**



10. Click on Add to attach a new .iso file.



11. Browse to the location of the new VST-VRT-x.x.x.iso file. Select it and click Open.

😚 Please choose a virtual c	pptical disk file			×
← → ~ ↑ ↓ → Ti	nis PC > Downloads		✓ Ö	arch Downloads
Organize 🔻 New fold	ler			EE 🕶 🔲 ?
★ Quick access Desktop ★ ↓ Downloads ★	Name V Today (2) VST_VRT-x.x.x.iso	Date modified 8/16/2021 9:28 AM	Type Disc Image File	Size
🖹 Documents 🖈 🧹	V SI_VKI-x.x.x-new.iso	8/10/2021 9:28 AM	Disc Image File	al optical disk files (*.dr v Cancel



🍀 AT-VST-VRT-x.x.x -	Settings	? ×
General	Storage	
System	Storage Devices	Attributes
Display	Controller: IDE	Optical Drive: IDE Secondary Device 0 IDE Secondary Device 0 IDE CD/DVD
Storage	Controller: SATA	Information
🕩 Audio	AT-VST-VRT-x.x.x-disk001.vdi	Type: Image Size: 1.06 GB
P Network		Location: C:\Users\andrewme\Downloads\V
🚫 Serial Ports		Attacied to.
<i> </i> USB		
Shared Folders		
User Interface		
	🔄 🗐 🔕	
		OK Cancel

12. In the Storage Tree view, you should now see the VST-VRT .iso is mounted.

13. OPTIONAL: Upgrading VST-VRT will not change the name of your VM. If you want to change the name to reflect the new software version, you can select the **General** tab in the **Settings** dialog, and change the name manually.

🔅 AT-VST-VRT-x.x.x -	Settings	?	×
General	General		
System	Basic Advanced Description Disk Encryption		
Display	Name: AT-VST-VRT-x.x.x		
Storage	Type: Linux	-	2.6
🕩 Audio	Version: Linux 2.6 / 3.x / 4.x (64-bit)	•	
Network			
Serial Ports			
DSB			
Shared Folders			
User Interface			
	ОК	Car	ncel





14. Restart the VM. To do this, right click on the VM, then select **Start** and **Normal Start**.

15. Once the VM is running, the upgrade of the VST-VRT software is complete.



16. To verify the currently running software version, login to your VST-VRT Web GUI, navigate to the System > About page, and look at the details there. The Software Version should agree with the VST-VRT Web GUI version.



Upgrade Vista Manager, AMF Cloud, Trap Receiver and AMF Security applications

VST-VRT version 3.4.1 and later (VST-VRT Operating System 1.5.1 and later) supports simpler upgrade of these applications as a bundle. This ensures they are compatible with each other and with the operating system version.

Before upgrading these applications:

- "Upgrade the VST-VRT operating system and GUI" on page 6
- we recommend backing up application data for all applications regularly, and before upgrading the applications.

Use the procedure in this section to dynamically upgrade these applications:

- Vista Manager
- AMF Cloud
- Trap Receiver plug-in
- AMF Security
- 1. In the VST-VRT Dashboard page, click the Upgrade Instances button.

æ	Dashboard					_			
⊕	Network Infrastructure $$	System Info	ormation						
*	User Management	CPU	15.40%						
\$	System ~	Temp	16.8%						
D	Vista Manager	Fans	Status: A	ctive					
D	AMF Cloud	Environment	Status: G	lood					
D	AMF Security	System Time	③30/06/20	22, 2:15:03 pm					
D	Wireless Controller	Deployed A	pplications						Upgrade Instances
D	Trap Receiver	Name		Image	CPU Load (%)	Memory (MB)	Storage (MB)	State	
D	SNMP Plug-in	AMF-Sec-ap	q	â sesc	0.08/100	227 / 32016	703 / 10000	Running	C Open
		AT-AMF-app		C 🔒 AMF	0.02/100	101 / 32016	258 / 10000	Running	C Open
		AT-AWC-app	0	🕐 🔒 awc	0.10/100	570 / 32016	846 / 10000	Running	C Open
		AT-FULLSNI	MP-app	â fullsnmp	0.03/100	431 / 32016	390 / 10000	Running	C Open
		AT-Vista-ap	D	C 🔒 vista	0.77/100	4291 / 32016	4608 / 204800	Running	C Open



2. Make sure the correct version of the bundle file is displayed in the **Upgrade to** field at the top left of the upgrade instances panel. If not, use the drop down list to select the correct version.

Applications that can be upgraded are shown as selected. We recommend upgrading them all.

Upgrade Instances	S					×
Upgrade To: VST				~		
Instance	State	Image	Current Version	Target Version	Status	Action
AT-AMF-app	Running	AMF	5.5.	5.5.2-01	This instance can be upgraded	
AT-AWC-app	Running	awc	3.	3.8.7	This instance is running an image that cannot be upgraded to the one in this bundle	
AT-FULLSNMP- app	Running	fullsnmp	2.	2.	This instance is running an image that cannot be upgraded to the one in this bundle	
AMF-Sec-app	Running	sesc	2.	2.	This instance can be upgraded	
AT-Vista-app	Running	vista	3.	3.	This instance can be upgraded	
					3 Upgrade	Selected

- 3. Click the **Upgrade Selected** button and wait till upgrade is complete. The **Status** column shows progress. They first stop, then change to the new version, then start.
- 4. It is important to save the state of the VST-VRT operating system after the upgrade. The **Save** button in the top right corner of the screen is orange when there are unsaved changes. Click on the button to save the changes .

Up time: 0 days 00:13	💄 Admin	Save

If you do not save and VST-VRT is rebooted, the upgraded applications will revert to the old app images and fail to start. You will see 'configured image "<image-name>" doesn't exist' messages if this happens.

 Vista Manager EX may prompt you to migrate the database. Select Download Database Backup to make a backup. Select Download Database Backup to make a backup.

Allied Telesis	Vista Manager™ EX
Vista Manager EX requires database	migration
Your Vista Manager EX data will be mig Please download a backup of your curre	ated automatically. nt data before proceeding.
Download Database Backup	Continue Migration



6. Confirm you have successfully downloaded a backup file, then select **Continue Migration**. If you get a browser error about the page becoming unreachable, then refresh your browser.

Allied Telesis Vista Manager™ EX	
Please confirm you have downloaded a backup	
Data may be lost during the migration process. If you have not yet downloaded a database backup, please do the previous page.	so in
< Back Continue Mi	gration
Allied Telesis Vista Manager™ EX	
Migration in progress	
O Database migration in progress. Please wait for Vista Manager to	o restart.

7. Once the migration has completed, your connection may be lost. If this happens, close your browser and reopen the application from the VST-VRT dashboard.



Upgrade Wireless Controller (AWC) and SNMP (full) plug-in applications

Use this manual procedure to upgrade the following applications by destroying the old and creating new instances.

Before upgrading these applications, "Upgrade the VST-VRT operating system and GUI" on page 6.

For AWC and SNMP (full) applications, you cannot:

- upgrade these as part of a set
- use the upgrade procedure from versions earlier than VST-VRT 3.4.1.
- use the Upgrade button in the VST-VRT GUI to upgrade.

Instead, use these procedures:

- "Back up application data" below
- "Destroy and recreate the application instances" on page 16
- "Re-register plug-ins in Vista Manager" on page 18
- "Restore application data from back-up" on page 19.

Back up application data

Before upgrading the Wireless Controller and SNMP Full applications, you must back up their system data. The procedures for this are described in this section. We recommend also backing up other applications. The procedures are similar.

Make sure that directories and filenames used for backup and restoration do not contain any multibyte characters.

Back up system data for the Wireless Controller (AWC) plug-in application

- 1. Log into Vista Manager EX using an Admin account.
- 2. From the AWC Plug-in menu, select System Setting.
- 3. To create a backup file for the log data in addition to the other data backup, check the **Include Log Data** checkbox to the right of the Backup button under System Maintenance (optional).
- 4. To start the back-up downloading, click the **Backup** button in the System Maintenance section.
- 5. From your web browser's dialog box, save the backup file to your local computer.

The backup filename will be in the format: "config_atawc-X.X.X_-YYYYMMDDhhmmss.zip".

Back up system data for the SNMP plug-in application

1. Log in to Vista Manager EX using an Admin account.



- 2. Click the **SNMP Plug-in** icon in the left menu of the Vista Manager application, then click the **System** menu.
- 3. In the **System Maintenance** panel of the **System Setting** page, click the **Backup** button. This creates a backup of application data.

Destroy and recreate the application instances

Follow these steps.

 In the application page for each application, hover over the Instance Information icon (i) and record information about the application from the Instance Information panel. Record all the Network settings (Network Type, etc).

⊕	Network Infrastructure 🗸	Wireless Controller						
*	User Management	Allied Telesis Autonomous Wave Control (AWC) is an advanced networ performance while reducing deployment and operating costs. By auton						
*	System ^	For me	ore information o	contact your local	ges and bandwid Allied Telesis sa	itn demands fr les representa		
	Backup and Restore	lmag	je server po Instance Infor	Il interval: mation: AT-AWC-	Disabled app Configu	ıre		
	Logging	Dej	Name	AT-AWC-app				
	Monitor Time		Compute ID	A-102549720229		(MB)		
	About	0	Image	awc 3.	Upgrad	975		
D	Vista Manager	U	Network: eth0	Network Type: VLAN ID: 1	Virtual			
D	AMF Cloud			MAC: 02:75:3E IPv4 Address:	3:83:BE:C3			
	AMF Security			DHCP: true				

- 2. In the application page, stop the application by clicking the **Stop** button.
- 3. Destroy the application by clicking the **Destroy** button.
- 4. Click the **Activate** button.



AWC:

204 800 MB

SNMP Full: 102 400 MB

5. In the **Application Configuration** dialog box, fill in the storage and prerecorded network data. The recommended storage values are:

-	Allied lei	esis VSI-			Up time: 0		Admin
æ	Dashboard	Wireles	s Controller				
	Network initiastructu						
*		Application Configuration			×	/ that utilized d performa	es Artificial nce while
۵	System	Compute ID		A-12238F-222294	~	os and Acce ork configu	ess Point ration changes
	Vista Manager	Image Version		3	3.8.0	ur local Alli	ed Telesis office
	AMF Cloud	awc-3.			^		
	AMF Security	awc-3.					
D	Wireless Controller	Storage Size (MB)			~	4	🌣 Activate
	Trap Receiver	204800 5					
	SNMP Plug-in	Advanced Settings			~		
		Network	1 N	etwork / 0 DNS Ser	rvers		
		Interface Type Virtual	5		Delete		
		External Network VLAN ID	MAC Address (Optional)				
		Use DHCP	UZ:75.3B:83:BE:C3				
		+ Add Network					
		+ Add DNS Server			6		
				Cance	l Apply		

- 6. Click the **Apply** button. This creates a new version of the application instance. Wait a few minutes for this to start and for the **Open** button to appear.
- 7. It is important to save the state of the VST-VRT operating system after the upgrade. The **Save** button in the top right corner of the screen is orange when there are unsaved changes. Click on the button to save the changes.

Up time: 0 days 00:13	💄 Admin	Save

- 8. From the VST-VRT menu, navigate to the **Vista Manager** page and click the **Open** button. If necessary, wait for Vista Manager EX to perform its initial set up.
- 9. Log in to Vista Manager EX.



Re-register plug-ins in Vista Manager

If you are using these plug-ins in Vista Manager EX, you will need to reregister them:

- Wireless Controller (AWC)
- SNMP (Full)

Follow these steps for each of the plug-ins.

- 10. On the Vista Manager EX page, navigate to **System Management** > **Plugins**.
- 11. Click **AWC Plug-in** at the bottom left.

≡	Allied Telesis Vista Manager	EX	Q Search network	😫 manager 👻
:: ::	System Management			Tech Support
⊕ ∦ [™]	About	Plugins		
ھ ن	Network Configuration	Vista Manager's Certificate Fingerprints	Re	generate Certificate
•	Resource Management	SHA1 0F:03:9F:11:A3:E3:13:A5:80:E7:49:70:08:56:25:1F:F7:52:31:F5		
٥	Database Management	SHA256	5-37-0E-31-45-48-EE-R2	
**	Licenses		5.57.61.51.R5.R5.1 E.52	
*	Plugins	Pluging		
		AWC Plug-in		T Add Plugin

If the plug-in is not registered, Vista Manager displays an error message like this:

	Allied Telesis Vista Manager™ EX
ł	Error occurred
	error
	Vista has encountered an error connecting to the plugin {"code":"DEPTH_ZERO_SELF_SIGNED_CERT"}

12. Click on the plug-in name and then **Edit**.

Plugins	+ Add Plugin
AWC Plug-in	Delete Plug-in Edit



13. Check the certificate and click **Save**. A 'Plug-in updated' pop-up message confirms this step.

Register Plugin	×
Server URL	
https:// :5443/wireless_plugin	
Please verify these certificate fingerprints match the ones the plugin i See Vista Manager EX Installation Guide for more information.	is reporting.
Plugin Certificate Fingerprints:	
SHA1	
28:69:65:21:F5:16:1E:62:FF:CD:EE:D7:89:6F:3B:A1:DC:81:35:CF	
SHA256	
D9:22:35:F5:7B:47:14:70:69:A6:E8:19:55:0B:7E:14:D5:27:52:0B:E8:1E:A1:C5 :90:32:ED:95	:4A:71:21:9D
	Save

- 14. Repeats Step 11 to Step 13 for the SNMP (full) plug-in.
- 15. Restore system data for the plug-in application from the back-up file ("Restore application data from back-up" below).

Restore application data from back-up

For the Wireless Controller and SNMP (Full) applications, you must use the following procedures to restore the system data:

- "Restore system data for the Wireless Controller plug-in" below
- "Restore system data for the SNMP plug-in" on page 20

Note that for the applications upgraded as a set in this procedure "Upgrade Vista Manager, AMF Cloud, Trap Receiver and AMF Security applications" on page 12, the data is restored automatically.

Restore system data for the Wireless Controller plug-in

Note that restoring a backup file made on another platform is not supported.

To restore data from the back-up file for the Wireless Controller (AWC) plug-in application, follow these steps:

- 1. Log in to Vista Manager EX using an Admin account.
- 2. In the Vista Manager EX menu, navigate to AWC Plug-in > System Setting page.

- 3. Click the **Restore** button in the System Maintenance section to open the **Restore** dialog box.
- 4. Click the Select File button and select a backup file.
- 5. Click Run.
- 6. Click **OK** on the confirmation dialog box.
- 7. After the restoration process has finished, a dialog box shows that restoration is complete. Click **OK**.

Note that the back-up cannot restore the following system information. Re-configure these values as necessary:

- « Database Setting > Maximum Memory Usage
- « Network Map Setting > Wireless Client Update-Interval

Note that an email server and "from" address must be configured on the device in order for email logs to work. Use the command **mail from <email-address> server <ip-address>**, where the <email-address> is the 'From:' field on the sent email, and the <ip-address> is the email's destination SMTP server.

Set the external IP address for the plug-in application. To do this, in the Vista Manager EX page, navigate to AWC Plug-in > System Setting.
 In the IP Address Settings page, click the drop down list and select the AWC IP address (don't select 'other').
 Click the Save button for that section.

Restore system data for the SNMP plug-in

To restore data from the backup of application data for the SNMP plug-in application, follow these steps.

Log in to Vista Manager EX using an Admin account.

- 1. In the left menu of Vista Manager EX, click the **SNMP plug-in** icon, then click the **System** menu.
- 2. In the **System Setting** page **System Maintenance** panel, click the **Restore** button. This restores the data from the back-up into the SNMP plug-in application.

🔨 🖉 Allied Telesis

NETWORK SMARTER

North America Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895 Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830 EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2023 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.